

EPICa

EP-2129J-S3S3

JBOD enclosure solution



The EPICa EP-2129J-S3S3 is Proware's most versatile SAS/SATA II Disk Expansion system, ideal for midrange and high capacity storage in Windows environments. Based on 3Gb SAS Channel host interfaces, the EP-2129J-S3S3 supports the choice of SAS (Serial Attached SCSI), and SATA II (Serial ATA) drive configurations to deliver a system bandwidth of up to 700MB/sec.

The ability to mix SAS and SATA drives allows the EP-2129J-S3S3 to be used for a range of applications that require different price/performance characteristics. Cost-effective SATA drives can be selected for capacity oriented storage such as disk-to-disk backup and the storage of reference data. Higher specification SAS drives can be employed for I/O intensive applications including transactional databases. Hosting multiple tiers of data in an EP-2129J-S3S3 configuration gives organizations the flexibility to meet both their technical requirements and budgetary constraints with a single unified solution.

Features

- ◆ Fully redundant with hot swappable disks, cooling fans and power supplies
- ◆ Modular Design With Common Parts
 - Inventory control efficiency
 - Cost-saving benefits to the end-user
- ◆ Power Supply
 - Power Supply and cooling system contained in 1 module for efficient cooling
 - 400W power supplies to meet the future HDD power consumption
- ◆ Enclosure
 - Modules are interchangeable with other Epica products
 - Hardware expansion slots keeps you up-to-date on the latest technologies
 - Incorporates a cableless design for maximum signal integrity
- ◆ SES
 - Utilizes industry-standard SCSI Enclosure Services to monitor enclosure and disk environmental conditions

SERIES TECHNICAL SPECIFICATIONS

Model	EP-2129J-S3S3
Form Factor	2U 19" rackmount chassis
Host Bus Interface	4 Lane SAS (Infiniband) Up to 300 MB/s per Channel
Disk Bus Interface	3.0 Gb SAS SAS / SATA II
Backplane	3Gb SAS Single BP
# of Hot Swap Trays	12
Tray Lock	Yes, w/ Lock Indicator
Disk Status Indicator	Access / Fail LED w/ 170° view
Capacity	4.8 TB (at 400GB SAS drive) 12 TB (at 1TB SATA drive)
Enclosure Monitoring (SES)	In Band SES via SAS
# of PS/Fan Modules	400W x 2 w/PFC
# of Fans per Module	1 (Multi-speed)
Max. Air Flow	160 CFM
Power Status Indicator	Yes
Fan Status Indicator	Yes
Power Requirements	AC 90V ~ 264V Full Range 8A ~ 4AV, 50Hz ~ 60Hz
Relative Humidity	10% ~ 85% Non-condensing
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Physical Dimension	577.5(L) x 495(W) x 88(H) mm
Weight (Without Disk)	14 Kg

Specification are subject to change without notice.

All company and product names are trademarks of their respective owners.

Serial Attached SCSI Advantages

Four-wire Replacement for Parallel SCSI	
• Software compatible "drop in" replacement	• Low voltage (1600 mV max) differential signaling (8b10b encoding)
"Star" Topology (Point-to-Point)	
• Each device gets full bandwidth	• Minimum arbitration overhead
SAS Attributes Extend Capabilities beyond Parallel SCSI	
• Dual-porting	• Native support for either SATA or SAS drives
• 16K devices (per domain)	• Wide ports and rate matching



PROWARE TECHNOLOGY CORP.
Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975
<http://www.proware.com.tw> E-mail:info@proware.com.tw

Your Storage Solutions Partner